

VS-K12 series portable industrial endoscope

Micro USB
TF card
HDMI port

Screen

Multiple colors available

- Black
- Grey
- Orange

⏻ ON/OFF/Screen freezes button

📷 Photo/Video

▲ UP/Flip /view switch button

☰ OK Menu/OK button

💡 Brightness adjustment
Delete button

↶ Return/Playback

▼ Down/Zoom button

Probe
(160000 resolution,
no articulation)

Power

Insert tube (Length for
optional)

Professional industrial endoscope solution supplier

To be as your wish

More efficient detection

VS-K series is equipped with a number of detection functions, with advanced technology, and comprehensive functions, which assists the inspectors to complete the inspection work efficiently.



Optical fiber illumination for clearer images

0.95-8mm
Various probe diameters are available



More probes for optional



Quick to change probes



5 inch screen, more convenient to watch



WIFI wireless transmission (for optional)








Temperature warning (for optional)

Host	Dimension	350*155*59mm
	Display	5 inch industrial touch LCD screen
	Output port	HDMI video output, Micro USB、TF card slot
	Storage	32G
	Power	Special rechargeable lithium battery pack, online charging, battery life \cong 4 hours
	IP grade	IP54
	Working temperature	-10°C~50°C
	Storage temperature	-20°C~60°C
	Relative humidity	Max 95%, No condensation
System	Operation System	Multifunctional operating system
	Operation method	Button navigation, dual camera and video buttons
	Support Function	With freeze, zoom, photo, flip, video playback, analog ruler functions
	File Format	Image:JPEG (JPG), Video:AVI
	Support Language	Chinese (Simplified and Traditional), French, English, German, Spanish, Italian, Japanese
Packing Case	Weight	3.9kg
	L*W*H	47.9*38.7*15.5cm









Camera and Probe

There are several length and diameter for VS-K12 series for you to chose according to your requirement.

Model		VS-K12		
		VS-K1210	VS-K1220	
Lens	Direction	Direct view		
	View angle	120°		
	DOF	3mm~30mm		
	Pixel	160000		
	Illuminating system	Rear high-power LED fiber optic transmission		
Probe	Length(L)	/		
	Diameter(D)	1.2mm		
	Articulating	No Articulating		
	Brightness of Illumination	1m	1m<L≤2m	
		≥10000Lux	≥8000Lux	
	Working temperature	-20°C~70°C		
Inserting tube	Length	1m	2m	
	Material	Bourdon tube		

VS-K (Direct view)	
Lens direction	
View angle(θ)	
DOF	
Probe Length(L)	
Probe diameter(D)	

Packing list

No	Name	PCS	Unit	Photos
1	Host	1	pcs	
2	Battery	1	pcs	
3	Packing Cast	1	pcs	
4	Memory Card	1	pcs	
5	Card reader	1	pcs	
6	Tripod	1	pcs	
7	USB cable	1	pcs	
8	Charger	1	pcs	
9	Warranty card	1	pcs	 <p style="text-align: center;">Warranty Card</p>
10	User manual	1	pcs	<p style="text-align: center;">Industrial Endoscope</p> 
11	Guarantee Card	1	pcs	 <p style="text-align: center;">QUALIFIED CERTIFICATE</p>