

VS-K39 series portable industrial endoscope




Professional industrial endoscope solution supplier

To be as your wish

More efficient detection

VS-K series is equipped with a number of detection functions, with advanced technology, and comprehensive functions, which assists the inspectors to complete the inspection work efficiently.




Optical fiber illumination for clearer images

0.95-8mm
Various probe diameters are available



More probes for optional



Quick to change probes



5 inch screen, more convenient to watch



WIFI wireless transmission (for optional)
















Temperature warning (for optional)

Host	Dimension	350*155*59mm
	Display	5 inch industrial touch LCD screen
	Output port	HDMI video output, Micro USB、TF card slot
	Storage	32G
	Power	Special rechargeable lithium battery pack, online charging, battery life \geq 4 hours
	IP grade	IP54
	Working temperature	-10°C~50°C
	Storage temperature	-20°C~60°C
System	Relative humidity	Max 95%, No condensation
	Operation System	Multifunctional operating system
	Operation method	Button navigation, dual camera and video buttons
	Support Function	With freeze, zoom, photo, flip, video playback, analog ruler functions
	File Format	Image:JPEG (JPG), Video:AVI
Packing Case	Support Language	Chinese (Simplified and Traditional), French, English, German, Spanish, Italian, Japanese
	Weight	3.9kg
	L*W*H	47.9*38.7*15.5cm







Camera and Probe

There are several length and diameter for VS-K39 series for you to chose according to your requirement.

Model		VS-K39						
		VS-K3910	VS-K3920	VS-K3930	VS-K3940	VS-K3950	VS-K3960	
Lens	Direction	Direct view/Side view/Double view						
	View angle(θ)	120°						
	DOF	8mm~150mm						
	Pixel	1MP						
	Illuminating system	Rear high-power LED fiber optic transmission						
Probe	Length(L)	Direct view/Side view: 12±0.5mm						
		Double view: 19±0.5mm						
	Diameter(D)	3.9mm						
	Articulating	360° full direction articulation						
	Bending Angle(α)	170°±10°	150°±10°	130°±10°	110°±10°	90°±10°	60°±10°	
	Brightnes s of Illuminat ion		1m	1m<L≤2m	2m<L≤4m		4m<L≤6m	>6m
		Direct view	≥60000Lux	≥50000Lux	≥40000Lux		≥30000Lux	/
		Double view	≥40000/10000Lux	≥30000/10000Lux	≥20000/10000Lux		/	/
	IP grade	IP67						
	Working temperature	-20°C~70°C						
Insert tube	Length	1m	2m	3m	4m	5m	6m	
		Double view: 3m						
	Material	Flexible (tungsten braided tube)						

	VS-K (Direct View)	VS-KC (Side view)	VS-KS (Double view)
Lens direction			
View angle(θ)			
DOF			
Probe Length(L)			
Probe diameter(D)			
360°articulation			
Bending angle(α)			

Packing list

No	Name	PCS	Unit	Photos
1	Host	1	pcs	
2	Battery	1	pcs	
3	Packing Cast	1	pcs	
4	Memory Card	1	pcs	
5	Card reader	1	pcs	
6	Tripod	1	pcs	
7	USB cable	1	pcs	
8	Charger	1	pcs	
9	Warranty card	1	pcs	 <p style="text-align: center; font-size: small;">WARRANTY CARD</p> <p style="text-align: center; font-size: x-small;">SHENZHEN VANDT CO., LTD.</p>
10	User manual	1	pcs	 <p style="text-align: center; font-size: small;">Industrial Endoscope User Manual</p>
11	Guarantee Card	1	pcs	 <p style="text-align: center; font-size: x-small;">QUALIFIED CERTIFICATE</p> <p style="text-align: center; font-size: x-small;">MODEL: _____ DATE: _____ INSPECTOR: _____</p>